



# MODEL 3722



## FEATURES

### Model 3722


The premium Model 3722 is for commercial and industrial facilities where demanding conditions require a rugged door that is also energy efficient.

- 20 gauge flush exterior steel skin.
- Full 2" thick sandwich construction consisting of exterior and interior steel skins filled by foamed-in-place polyurethane foam.
- **A GREEN DOOR:** Clipay's polyurethane foam is CFC and HCFC free and utilizes recycled steel and packaging materials.
- Both steel skins are separated by a continuous foam thermal break.
- Clipay's three stage prepainting process yields a durable, maintenance-free finish.
- Stucco embossed flush exterior; interior steel skins with micro-grooved ribs.
- Foamed-in-place polyurethane insulation; section R-value 17.2.



#### Rust-resistant

Panels are prepainted inside and out to inhibit rust. Hot-dipped, galvanized steel is painted with primer and given a tough oven-baked polyester top coat, to provide the most rust-resistant steel door available. Ten year warranty against rust-through.



#### Flush Panel Design





# CLOPAY MODEL 3722

## 20 GAUGE HEAVY-DUTY 2" STEEL FOAMED-IN-PLACE, THERMALLY BROKEN DOORS

**Quality Assurance** – Doors shall be insulated steel sectional overhead type as manufactured by Clopay Building Products. Each door is provided as one complete unit including sections, brackets, tracks, counterbalance mechanisms, and hardware (list options) to suit the opening and headroom available. Standard maximum size is 26'2" wide and 20' high.

**Materials and Construction** – Sections shall be 2" thick sandwich construction consisting of exterior and interior steel skins filled with foamed-in-place polyurethane foam. Both steel skins to be separated by a continuous foam thermal break. Steel skins, with stucco embossed texture, shall be roll formed commercial quality hot-dipped galvanized per ASTM A-294, A-653, phosphate coated, prepainted with primer and baked-on polyester top coat. Exterior door sections are constructed of .034" min. (20 gauge) flush steel, and interior door sections are .016" min. (27 gauge) steel with .040" minor rib, 4" or 5" on center. End stiles shall be .045" (18 gauge) galvanized steel. All stiles are engineered for easy hardware attachment. 16 gauge (.056" min.) double end stiles as required. 19 gauge hinge back-up plates for hinge attachment. Full length aluminum retainer with U-shaped flexible PVC vinyl astragal. Section joint to form a weathertight tongue-and-groove joint. Steel step plate/lift handle provided on bottom section. SECTIONS GUARANTEED AGAINST DELAMINATION FOR TEN (10) YEARS.

**Energy Value** – Section R-value = 17.2\*

\*Calculated door section R-value is in accordance with DASMA TDS-163.

**Finish** – The section exterior and interior is prepainted steel consisting of a hot-dipped galvanized coating applied to the base metal. A phosphate treatment is applied before a baked-on primer. This prime coat is finished with a polyester coat for rust protection. The exterior skin carries a 750 hour salt spray rating. The interior portion of the skin that is adhered to the polyurethane foam is a baked-on coating. Doors are available in white or brown exterior finish. FINISH GUARANTEED AGAINST RUST-THROUGH FOR TEN (10) YEARS.

**Hardware** – All hinges and brackets to be manufactured of hot-dipped galvanized steel, 14 gauge minimum. Ten ball steel rollers to be full floating ball bearing in case-hardened steel races, mounted to fit the taper of the track.


**Tracks** – 2" or 3" track. Vertical tracks to be minimum of 16 gauge galvanized steel tapered and mounted for wedge type closing. Horizontal tracks to be minimum 14 gauge galvanized steel, reinforced with minimum 13 gauge galvanized steel angles as required. 3" track is 12 gauge.

**Spring Counterbalance** – Door assembly to be operated by a torsion spring counterbalance mechanism with a helically wound oil tempered torsion spring mounted on a galvanized steel tube or solid steel shaft as required. Cable drums are die cast aluminum with high strength galvanized aircraft cable with minimum 7 to 1 safety factor.

**Locking** – Inside spring loaded slide bolt lock on end stile shall engage slot in track.

**Wind Loading** – Door shall comply with ANSI/DASMA 108 or to meet specific application requirements.

DISTRIBUTED BY:



For special applications and options, consult Commercial Information Assistance (CIA) at 1-800-526-4301.

### OPTIONS

- A. Glazing** – 24" x 8" or 24" x 12" window lites of cellular PVC frame construction: available with 1/2" insulated, 1/2" insulated tempered, or 1/4" wire glazing options. Full vision section, prepainted white or brown; glazing options include 1/8" DSB, 1/8" tempered, 1/8" plexiglass, 1/2" insulated or insulated tempered, or 1/4" polycarbonate.
- B. High Cycle Spring** – Available in 25,000; 50,000; or 100,000 cycle.
- C. Track** – Vertical lift, high lift, follow the roof slope and low headroom track available, 2" or 3" as required.
- D. Weatherseal** – Complete perimeter seals available in various materials.
- E. Locking** – Five pin cylinder lock with outside key, 16-1/2" lock bar.
- F. Mullions** – Carry-away and roll-away available on doors to 14' high (2" track only). Swing-away available on doors to 20' high (2" and 3" track).
- G. Pass Door** – 32" wide x 80" high, maximum 16'2" wide section.
- H. Break-Away Bottom Section** – Single section available up to 20' 2" wide on doors with full vertical lift track or high lift track with minimum of 36" of high lift. Double sections available up to 14' 2" wide on doors with full vertical lift track or high lift track with minimum of 60" of high lift.

### Window Options (24" x 8" or 24" x 12" Windows)

Door Width	Max Number of Window Lites
Up to 9'2"	2
9'4" to 13'2"	3
13'4" to 16'2"	4
16'4" to 20'2"	5
20'4" to 24'2"	6
24'4" to 27'2"	7

### Section Arrangement

Door Height	Number of Sections
6'3" to 8'0"	4
8'3" to 10'0"	5
10'3" to 12'0"	6
12'3" to 14'0"	7
14'3" to 16'0"	8
16'3" to 18'0"	9
18'3" to 20'0"	10

